

**Village of Menomonee Falls Utilities
Meter Settings**

Size	Brand	Description	Flow Range	Lay Length	Screen	Connections
3/4"	Badger	Model 25	1/8 to 25 GPM	7 1/2"		Meter coupling 3/4 mpt x 1"
1"	Badger	Model 70	15 to 70 GPM	10 3/4"		Meter coupling 1" mpt x 1 1/4"
1 1/2"	Badger	Model 120	1.25 to 120 GPM	17 1/4"		1 1/2" fpt x 2" mpt bushing
2"	Badger	Model 170 Dsc	1.5 to 170 GPM	20 1/4"	-	2" fpt x 2 1/2" mpt bushing
2"	Badger	RCDL Compound	.5 to 200 GPM	17"	7"	4 - Bolt Round
2"	Badger	Compound Series	.5 to 200 GPM	15 1/4"	7"	4 - Bolt Round
2"	Badger	RCDL Turbo II	3 to 310 GPM	10"	7"	4 - Bolt Round
2"	Badger	Turbo Series	3 to 250 GPM	10"	7"	4 - Bolt Round
2"	Sensus	OMNI T-2	1 to 250 GPM	17"	Built In	2 - Bolt Elliptical
2"	Sensus	OMNI C-2	.25 to 200 GPM	17"	Built In	2 - Bolt Elliptical
3"	Badger	RCDL Compound	.5 to 450 GPM .5 to 450 GPM	17"	7"	4 - Bolt Round
3"	Badger	Compound Series	.5 to 450 GPM	17"	7"	4 - Bolt Round
3"	Badger	RCDL Turbo II	4 to 550 GPM	12"	7"	4 - Bolt Round
3"	Badger	Turbo Series	4 to 550 GPM	12"	7"	4 - Bolt Round
3"	Sensus	OMNI T - 2	1.5 to 650 GPM	17"	Built In	4 - Bolt Round
3"	Sensus	OMNI C - 2	.5 to 500 GPM	17"	Built In	4 - Bolt Round
4"	Badger	RCDL Compound	1.0 to 1250 GPM	24"	9"	8 - Build Round
4"	Badger	Compound Series	.75 to 1000 GPM	20"	9"	8 - Build Round
4"	Badger	RCDL Turbo II	8 to 1250 GPM	14"	9"	8 - Build Round
4"	Badger	Turbo Series	8 to 1250 GPM	14"	9"	8 - Build Round
4"	Sensus	OMNI T - 2	2 to 1250 GPM	23"	Built In	8 - Build Round
4"	Sensus	OMNI C - 2	.75 to 1000 GPM	23"	Built In	8 - Build Round
6"	Badger	RCDL Compound	1.0 to 1250 GPM	24"	9"	8 - Bolt Round
6"	Badger	Compound Series	.75 to 2000 GPM	24"	9"	8 - Bolt Round
6"	Badger	RCDL Turbo II	15 to 2650 GPM	18"	9"	8 - Bolt Round
6"	Badger	Turbo Series	15 to 2650 GPM	18"	9"	8 - Bolt Round
6"	Sensus	OMNI T - 2	2.5 to 2500 GPM	24"	Built In	8 - Bolt Round
6"	Sensus	OMNI C - 2	1.5 to 2500 GPM	24"	Built In	8 - Bolt Round